

HOOD TYPE DISHWASHER ELECTROMARICA BASKET 50x50 mod.. RIVER 483CDE DIM. mm.633x750x159H - THREE-PHASE 400V POWER. 10.2 kW.

Elettrobar River 483CDE Professional Hood Dishwasher (50x50 Basket)



SOLUZIONI FOODSERVICE

If you're looking for the ultimate in technology, hygiene, and efficiency for your business's dishwashing management, the Elettrobar River 483CDE is the answer. This 10.2 kW three-phase hood-type dishwasher combines extraordinary productivity with rock-bottom energy consumption, all managed by a next-generation touch interface. Thanks to its versatility, it is designed for both in-line and corner installation. The Strengths of Elettrobar Technology - Elettrobar Clean Construction: Built with a double-wall construction with an insulated hood (thermo-acoustic) to reduce noise and heat dispersion. The molded tank has no sharp edges or points where dirt can accumulate. Furthermore, the InSpect wash and rinse channels are easily accessible for lightning-fast daily cleaning. - SmartTouch & Wi-Fi Interface: A high-definition screen made of scratch-resistant synthetic glass (2 mm) displays temperatures, programs, and diagnostics. It includes the Point button that changes color based on the machine's status and is Wi-Fi ready. 15 Special Programs (Including Thermal Disinfection): A complete program suite for every need. Highlights include the thermal disinfection program for dishes (essential for maximum hygiene standards), 2 specific programs for washing bottles with the Bottlemaster rack, and the ProSoft soft start to protect the most fragile glasses and plates. - ELS Ergonomics: The hood's soft lifting system drastically reduces operator fatigue during the busiest shifts. - Record Consumption: Only 1.5 liters of water per cycle, a dramatic water and energy saving compared to standard models. TECHNICAL AND PERFORMANCE SPECIFICATIONS: - External Dimensions (W x D x H): 633 x 750 x 1590 mm - Basket Dimensions: 500 x 500 mm - Maximum Theoretical Productivity: Up to 60 baskets/hour - Water Consumption per Cycle: 1.5 Liters - Power Supply / Voltage: Three-phase 400V / 50Hz / 3N (Max Current 16 Amp) - Total Absorption: 10.2 kW (10,200 W) - Water Supply Pressure: 0.5 - 6.0 bar - Water Supply Temperature: Min 15°C - Max 60°C - Tank / Boiler Capacity: 20 Liters / 7 Liters - Tank / Boiler Heating Element: 2,500 W / 7,000 W - Wash Pump: 700 W - Rinse Pump: 200 W - Drain Pump: 200 W - Drain Pump: 200 W Drain: 40 W (Included) The River 483CDE is more than just a dishwasher; it's a smart, high-performance dishwashing station. It reduces detergent usage, consumes very little water, is quiet, and protects your most delicate glasses, ensuring thoroughly sanitized dishes in record time.