

STAINLESS STEEL TROLLEY WITH 20 SPACES FOR GN 1/1 TRAYS, CABINET VERSION

FRAME ON WHEELS WITH 20 PAIRS OF 'C' SLIDING GUIDES WITH BOTTOM SHEET AND DRAIN, FOR TRAYS AND TRAYS



CODICE: 0455804550121
MARCA: Chef secret



SOLUZIONI FOODSERVICE

CHARACTERISTICS:

- hollow-core door in full opening version
- handle with groove opening and magnetic closure
- sturdy hinges with 270° total opening for minimal space with the door open
- door closure with rotary latch
- perimeter panels in Aisi 304 stainless steel, bottom sheet with drain hole
- made entirely of Aisi 304 - 18/10 stainless steel
- 2 rear handling handles in plastic material
- square tubular structure cm. 2.5x2.5 TIG welded
- 12/10 thick "C" shaped guides
- 2 rear handling handles in plastic material
- pitch between the guides cm. 7
- bottom equipped with drainer
- stainless steel threaded block welded to the structure for fixing wheels
- wheels diameter cm. 12.5 with acid-resistant fibre-reinforced ABS supports screwed with stainless steel bolts
- payload kg. 135
- overall dimensions cm. 40x62 H174.5

Suitable for transporting plates, trays or tubs (gastronorm 1/1) up to a maximum of 20 pieces at the same time.

Ideal for large kitchens, canteens, supermarkets, butchers and other public and gastronomic facilities. Thanks to the careful workmanship and the stainless steel with which it is produced, the trolley is extremely easy to clean and maintain.

Stable, self-supporting and hygienic construction in TIG-welded square tubing, a spontaneous fusion welding process that guarantees high quality and excellent aesthetic results.

The "C" shaped support guides are welded diagonally to increase the load capacity and guarantee stability and maximum durability, with a gap of cm. 7 with anti-fall stopper.

Trolley equipped with 4 high-performance swivel wheels in anti-corrosion material, excellent smoothness and silence, made with polypropylene core and non-marking gray synthetic rubber tread, polyamide support structure and swiveling on double row of stainless steel balls, through-hole hub, 2 with brake, easily replaceable, fixing with stainless steel bolt on a threaded support welded to the frame, protected by 4 round bumpers in resistant plastic material, mounted directly above the wheels. They can be replaced by dismantling the wheels themselves.